



# WELDING POSITIONER GRIPPERS

PART No.	POSITIONER	O.D CAPACITY	I.D CAPACITY
WPG-22	WP500-2, WP1000-2, WP2000-4	25 - 381 mm	101 - 558 mm
WPG-26	WP1000-2, WP2000-4	38 - 457 mm	152 - 660 mm
WPG-34	WP2000-4	50 - 660 mm	152 - 863 mm



## Features

- Self Centering
- Reversible Jaws
- Easy Mounting

SPECIFICATIONS	WP250-2	WP500-2	WP1000-2	WP2000-4
Capacity Vertical	113 kgs	227 kgs	454.55 kgs	909.09 kgs
Capacity Horizontal	200 kgs	409 kgs	795.45 kgs	1590.9 kgs
Load Center of Gravity	100 mm	152 mm	152 mm	304 mm
Tilt	Manual	Power	Power	Power
Tilt Angle (Degrees)	0 - 90	0 - 135	0 - 135	0 - 135
Tilt Angle Indicator	N/A	N/A	N/A	Standard
Ground Capacity	200 amps	300 amps	500 amps	1000 amps
Grounding Device	Carbon	Brass	Brass	Rotary
High Frequency Protection	Yes	Yes	Yes	Yes
Volt / AC	115	115	115	440 3ph
Power Req.	5 amps	10 amps	10 amps	5 amps
Table Thickness	14 mm	22 mm	25 mm	25 mm
Table Diameter	349 mm	498 mm	622 mm	901 mm
Table Configuration	3 Slot	4 Slot	4 Slot	4 Slot
Optional Chuck	WPC11	WPG-22	WPG-22 & 26	WPG-22
Table Height (Horizontal)	335 mm	641 mm	855 mm	911 mm
Table Center Height (Vertical)	225 mm	539 mm	736 mm	781 mm
Through Hole	28 mm	N/A	N/A	N/A
Table R.P.M	0 - 5.5	0.4 - 4	0.2 - 2	0.2 - 1.2
Rotation Motor H.P	1/8 h.p	1/6 h.p	1/4 h.p	1 h.p
Variable Speed Rotation (meter- newtons)	Yes	Yes	Yes	Yes
Foot Control	Single	Fwd./ Rev.	Fwd./ Rev.	N/A
Max. Torque	468 nm	2714 nm	8142 nm	16284 nm
Hand Pendant	Optional	Optional	Optional	Standard
Anchor Points	4	4	6	6
Leveling Bolts	N/A	Included	Included	Included
Unit Width	317 mm	660 mm	819 mm	914 mm
Unit Length (meter- newtons)	533 mm	860 mm	1231 mm	1562 mm
Shipping Weight	51 kgs	236 kgs	545 kgs	7445 kgs