



## Here we Grow again....

Welcome to the first release of our Products Newsletter.

In each issue we will provide information on New Products, Promotions, Product Reviews and Updates on IWWS & people.

Our new IWWS Catalogue along with the new Profax & Lenco Catalogue 2009/2010 editions are on their way to you.

IWWS new website will be launched over the coming weeks. Our website will provide distributors with quick & easy access to our products, MSDS forms, New products & access for signing up to our E-newsletter.

For all enquires on any of our products or services ph: +61 2 9838 9866 or email [iwws@iwws.net](mailto:iwws@iwws.net)

## IN THIS ISSUE

### NEW PRODUCTS

Magswitch Range Pg 1

Tempil Infra Red Thermometer Pg 1

### PROMOTIONS

Jasic Welding Machines 5/10 Deal Pg 2

Mig Gun 10/15 Super Deal Pg 3

### PRODUCT REVIEWS

Speedway Torches Pg 4

Welding Positioners Pg 4

## CONNECTED WITH MAGSWITCH



Magswitch has created a powerful magnetic device that can be turned on & off with a simple turn of a knob. No batteries! No electricity!



**WELDING CLAMPS**  
Available in 200,  
300 & 600 amps



**MAG SQUARES**  
Available in 30,  
50 & 70 mm



**90° ANGLES**  
Available in  
30 & 50 mm



**BOOMERANGLES**  
Available in  
30 & 50 mm



**EXTEND A LIFT**  
Available in  
50 mm



**SINGLE LIFTER**  
Available in  
50 & 70 mm



**HEAVY DUTY LIFTER**  
Available in 70 mm  
Dual Lifter & Trilifter



**HANGING HOOKS**  
Available in  
30 mm Power hook  
50mm Gorilla Hook

## TEMPIL INFRA RED THERMOMETER



The industry's most advanced, non contact infrared technology based surface temperature measurement device.

It is lightweight, compact, easy to use.

### FEATURES

- 16:1 Distance to spot ratio
- Measurement Range: -60°C to 625°C
- Digital back lit dual display
- High temperature range
- Ergonomic hand grip
- °C or °F selectable read out
- Electronic trigger lock for continuous measurement
- Adjustable emissivity
- Laser sight switchable
- Min/Max/Avg and differential temperature modes
- Low battery indication and auto power off
- A built in jack for a K-Type thermocouple probe

**Part No:** IRT-16 Thermometer  
IRT-16NIST Thermometer with certification

\* INSTOCK 30TH MAY 2009



# JASIC WELDING MACHINES

## 5/10 PROMO

**PROMO**  
**STARTS JUNE 1st 2009**  
 and  
**ENDS JULY 31st 2009**

Buy any combination of 5 or more Jasic machines listed below, and receive 10% off the distributor 1\* net price

\* discount is off the distributor 1st price break

**NEW**

### ARC140

- Hot start & Arc force built in
- DC Tig welding with lift arc ignition
- Anti sticking
- Auto protection of over voltage and over current
- Auto compensation for voltage fluctuation
- AC240 Volt (Input power)
- Shoulder strap included
- 4m Lead kit included
- Dimensions(mm): 290(L) x 120(W) x 198(H)
- Weight: 4.7kgs



### ARC160II

- Industrial application
- High strength case construction of ABS material
- DC Tig Function
- Electrode hot start & arc force
- Excellent ARC stability
- Over voltage & thermal overload protection
- Tolerant to variable power supply
- Shoulder Strap included
- AC240 Volt (Input power)
- Dimensions (mm): 375(L) x 175(W) x 330(H)
- Weight: 7.6kgs



### JS180P

- ABS plastic enclosure
- HF start
- Anti-stick
- Choice of pulse function
- AC240 Volt
- Down slope time adjustable
- Excellent arc stability
- 2T/4T Trigger function
- Dimensions(mm): 375(L) x 175(W) x 330(H)
- Weight: 8kgs



### TC200AC/DC

- Rugged metal case construction
- 2T/4T Trigger function
- Adjustable AC balance control
- Adjustable pulse control
- Adjustable Pregas - Postgas
- Adjustable down slope
- HF start AC/DC Tig Function
- Tolerant to variable power supply
- Electrode hot start and adjustable arc force
- AC240 Volt (Input power)
- Dimensions (mm): 510(L) x 330(W) x 360 (H)
- Weight: 30kgs





# PROFAX MIG GUNS

## 10/15 PROMO

Buy any combination of 10 air cooled Mig and/or Flux Guns and receive 15% off the distributor 1\* net price.

\* Discount is off the 1st distributor price break

Note: All IWWS Terms & Conditions apply

### AIR COOLED MIG GUNS

#### 180 AMP MIG GUNS

180-3035-10	10 FT MIG GUN
180-3035-12	12 FT MIG GUN
180-3035-15	15 FT MIG GUN

For Euro end add X to the beginning of the part number  
For Lincoln/Hobart end add LH to the beginning of the part number

#### 250 AMP MIG GUNS

250-3035-10	10 FT MIG GUN
250-3035-12	12 FT MIG GUN
250-3035-15	15 FT MIG GUN

For Lincoln end add LN to the beginning of the part number  
For Flexi end add TF to the beginning of the part number  
For Flexi Euro end add TFX to the beginning of the part number  
For Euro end add TX to the beginning of the part number

### REASONS TO BUY PROFAX MIG GUNS

- Optimum Torch Cooling
- Robust Construction & Durability Extends Torch Life
- Contains more Copper in the Cable Providing Better Efficiency
- Outer Casing of Cable is Rubber with Cross Polymers Prevents "Running" when Pricked or Cut.
- Mig Guns have Four Trigger Leads (Two Spares)
- All Profax Guns have Adaptable Backends, Fit Most Brand Mig Machines
- Superior Fitting of the Copper Cable to Front & Rear Adaptor
- Eliminates the use of expensive adaptors
- Mig Gun Handles are Made of a High Heat Resistent Nylon with Fibre Glass Filling
- Copper Cable will not Twist Inside the Rubber Cable Hose

### FLUX CORE GUNS

\*Unique Feature - Liners are replaceable

#### 130 AMP FLUX CORE GUN

130GL-3035-12	SELF SHIELD GUN
---------------	-----------------

#### 350 AMP FLUX CORE GUNS

1260-10	10 FT
1260-15	15 FT

For Euro end add TX to the beginning of the part number



PROMOTION



#### 400 AMP MIG GUNS

400-116-12	12 FT MIG GUN
400-116-15	15 FT MIG GUN
400-3545-10	10 FT MIG GUN
400-3545-12	12 FT MIG GUN
400-3545-15	15 FT MIG GUN
400-3545-20	20 FT MIG GUN
400-3545-25	25 FT MIG GUN

For Lincoln end add LN to the beginning of the part number  
For Miller end add M to the beginning of the part number  
For Flexi end add TF to the beginning of the part number  
For Flexi Euro end add TFX to the beginning of the part number  
For Euro end add TX to the beginning of the part number

#### 500 AMP MIG GUNS

500-116-12	12 FT MIG GUN
500-116-15	15 FT MIG GUN
500-332-15	15 FT MIG GUN
500-3545-10	10 FT MIG GUN
500-3545-12	12 FT MIG GUN

For Lincoln end add LN to the beginning of the part number  
For Miller end add M to the beginning of the part number



#### 350 AMP FLUX CORE GUNS

2640-10	10 FT
2640-15	15 FT

#### 450 AMP FLUX CORE GUNS

1150-10	10 FT
1150-15	15 FT





Speedway high performance tig welding torches features a silver brazed copper construction which increases electrical current capacity and dissipates heat most efficiently giving long trouble free performance.



## HIGH PERFORMANCE TIG WELDING TORCHES



**Speed Bump™ Handle**  
Can rotate 360°



**Dual Back Cap Seal**  
Provides positive gas seal and protection against HF current leaks.



**Speed Nut™ Hose Connections**  
No tools or special hoses. Quick, easy repairs.



**High Performance Cable Assemblies**  
Soft, flexible over braided hose. Larger copper conductor.

Available in 320 amp, 418 amp & 450 amp torch body with 12 ft or 25 ft cable assemblies



## PROFAX

### WP250-2

- 340mm Diameter Table
- 0 to 5.5 rpm Rotation Speed
- Manual Tilt Adjustment
- 240 Volt
- 0-90° Tilting Angle
- High Frequency Protected
- Standard with Foot Control
- Designed for rotation of lighter pieces
- Will hold 200kgs in the horizontal position and 113kgs in the vertical position



### WP500-2

- 490mm Diameter Table
- 0.4 to 4 rpm Rotation Speed
- Power Tilt Adjustment
- 230 Volt
- 0-135° Tilting Angle
- High Frequency Protected
- Standard Fwd/Rev. Foot Control
- Will hold 409kgs in the horizontal position and 227kgs in the vertical position



### WP1000-2

- 612.5mm Diameter Table
- 0.2 to 2 rpm Rotation Speed
- Power Tilt Adjustment
- 230 Volt
- 0-135° Tilting Angle
- High Frequency Protected
- Standard Fwd/Rev. Foot Control
- Will hold 795kgs in the horizontal position and 454kgs in the vertical position



### WP2000-4

- 887.5mm Diameter Table
- 0.2 to 1.2 rpm Rotation Speed
- 415 Volt 3 Phase
- 0-135° Tilting Angle
- High Frequency Protected
- Standard Hand Control Pendant
- Will hold 2590kgs in the horizontal position and 909kgs in the vertical position

