

TIGMASTER®

CABLE COVERS

Double stitching of the closure to ensure long life.
Cable covers are fused to resist fraying and ty-straps are provided to secure the cable cover to the torch handle.

The non-conductive zipper/velcro closure allows installation of the cable cover without removing the torch from the welding machine. The non-conductive zipper will not conduct "HF" current and is protected from hot metal contact by the overlap flap construction.
Velcro closure is not affected by burn or melt spots.

Nylon



Nylon Covers - Flexible - Light Weight - Great Value

Part No.	Width x Length Imperial	Width x Length Metric	Seal
PX-3-10	3" x 10'	7.62 cm x 3 m	Zipper
PX-3-10V	3" x 10'	7.62 cm x 3 m	Velcro
PX-3-22	3" x 22'	7.62 cm x 6.7 m	Zipper
PX-3-22V	3" x 22'	7.62 cm x 6.7 m	Velcro
PX-3-48	3" x 48'	7.62 cm x 14.6 m	Zipper
PX-3-48V	3" x 48'	7.62 cm x 14.6 m	Velcro

Soft Leather



PX-4-10	4" x 10'	10.16 cm x 3 m	Zipper
PX-4-10V	4" x 10'	10.16 cm x 3 m	Velcro
PX-4-22	4" x 22'	10.16 cm x 6.7 m	Zipper
PX-4-22V	4" x 22'	10.16 cm x 6.7 m	Velcro
PX-4-48	4" x 48'	10.16 cm x 14.6 m	Zipper
PX-4-48V	4" x 48'	10.16 cm x 14.6 m	Velcro

Premium Soft Leather Covers

Part No.	Width x Length Imperial	Width x Length Metric	Seal
TCL-3-10	3" x 10'	7.62 cm x 3 m	Zipper
TCL-3-22	3" x 22'	7.62 cm x 6.7 m	Zipper

Split Leather



Split Leather Covers - Tough - Durable - Economic

Part No.	Width x Length Imperial	Width x Length Metric	Seal
TM410Z	4" x 10'	10.16 cm x 3 m	Zipper
TM410V	4" x 10'	10.16 cm x 3 m	Velcro
TM422Z	4" x 22'	10.16 cm x 6.7 m	Zipper
TM422V	4" x 22'	10.16 cm x 6.7 m	Velcro
TM832V	8" x 32'	20 cm x 10 m	Velcro *

* For Interconnecting Leads



INDEPENDENT WHOLESALE WELDING SUPPLY

Ph: 02 8834 2400 Fax: 02 8834 2498 Email: iwws@iwws.net Website: www.iwws.net